



APPROX DIAMETER 6.0 MM
±0.5 MM

CRAIGEARN BUSINESS PARK
MORRISON WAY
KINTORE, ABERDEENSHIRE
AB51 0TH
TEL : 44 1467 633780
FAX : 44 1467 631284

WEB: WWW.1ST4CABLES.COM / E-MAIL: SALES@1ST4CABLES.COM

COMPONENT DETAILS :

FIBRE TUBE DIAMETER 3.0 MM

PHYSICAL DETAILS :

OVERALL DIAMETER 6.0 MM
R.T. OUTER SHEATH 1.0 MM
WEIGHT OF CABLE IN AIR 53 KG/KM
MINIMUM BEND RADIUS (STATIC) 60 MM
MINIMUM BEND RADIUS (DYNAMIC) 90 MM

WORLDWIDE LTD

SHF2 STANDARDS COMPLYING :

IEC60092/351 HF90
IEC60092 SHF2

CABLE CONSTRUCTION		
ITEM	DESCRIPTION	QTY
A	FIBRE OPTIC CABLE (GEL FILLED PBT TUBE CONTAINING 2 X SM 9/125 + 2 X MM 62.5/125 FIBRES, COLOUR CODED FOR IDENTIFICATION)	1
B	GALVANISED STEEL WIRE BRAID	
C	SHF2 OUTER SHEATH	

ISSUE NO. :	DATE	DRG. NO. HS-SK 1258
01	16/03/17	DRWG NOT TO SCALE

FLEXIBLE SOLUTIONS FOR HARSH ENVIRONMENTS

THIS DRAWING AND INFORMATION IS COPYRIGHT TO CABLE SOLUTIONS WORLDWIDE LTD
THEREFORE INFORMATION MAY NOT BE USED WITHOUT WRITTEN PERMISSION FROM CABLE SOLUTIONS WORLDWIDE LTD

DRWG BY : D.GILL