



FIBRE OPTIC CABLE, TIGHT BUFFER, 4 SINGLEMODE FIBRES (9/125)

GALVANISED STEEL WIRE BRAID

ZERO HALOGEN, FLAME RETARDANT POLYURETHANE SHEATH (R.T 1.5 MM)

APPROX DIAMETER 10.6 MM ±0.5 MM

CABLE CONSTRUCTION :

FIBRE OPTIC, TIGHT BUFFERED CABLE (4X9/125, SINGLEMODE) + GSWB + PUR OUTER SHEATH (R.T 1.5 MM)

APPROX. COMPONENT DETAILS :

DIAMETER OF COAXIAL 6.5 MM

PHYSICAL DETAILS :

**OVERALL DIAMETER 10.6 MM
LAYED UP SIZE OF CABLE N/A MM
R.T. PU SHEATH 1.5 MM**

**WEIGHT OF CABLE IN AIR 108 KG/KM
WEIGHT OF CABLE IN WATER 18 KG/KM**

BEND RADIUS :

**STATIC 127 MM
DYNAMIC 159 MM**

CABLE & DATA SOLUTIONS

GROUP LTD

FLEXIBLE SOLUTIONS FOR HARSH ENVIRONMENTS

THIS DRAWING AND INFORMATION IS COPYRIGHT TO CABLE & DATA SOLUTIONS GROUP LTD THEREFORE INFORMATION MAY NOT BE USED WITHOUT WRITTEN PERMISSION FROM CABLE & DATA SOLUTIONS GROUP LTD

DRAWING NO : HS-SK 665

ISSUE NO : 1 DRWG NOT TO SCALE

DRWG BY : D.GILL